

UNI-T®

2009

Uni-Trend Your Testing Specialist !



Certificate No.: QAC0956661



UT4000 SERIES

Digital Storage Oscilloscope (Full Colour)

UT4042C • UT4062C • UT4082C



SPECIFICATIONS

NEW

Features	UT4042C	UT4062C	UT4082C
Bandwidth	40 MHz	60 MHz	80 MHz
Rise Time	<8.7 ns	<5.8 ns	<4.5 ns
Sample Range		2GS/s	
Vertical Sensitivity		2mV ~ 5V/div	
Record Length (Max)		1024k	
Sample Rate		Real time 1GS/s, Equivalent: 25GS/s	
Scan Time Base	10ns ~ 50s/div	5ns ~ 50s/div	5ns ~ 50s/div
Trigger Type		Edge, Pulse, Video, Slope and Alternate	
Automatic Waveform Measurements		28	
Ports		Standard: USB Device, USB Host ; PASS/FAIL Optional: LAN and GPIB	
Mathematics		Add, Subtract, Multiply, Divide, Reverse and FFT	
Applications		College Education, R&D, Electronic product assemble line, Industrial Control etc.	
Other Features		Digital Multimeter and Logic Analyzer	

GENERAL CHARACTERISTICS

Power	100 - 240VAC _{RMS} , 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Colour	Red and Grey, White and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm (wide) x 165mm (high) x 165mm (deep)
Standard Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe x 1, Multimeter Probe x 2, Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	480 x 440 x 300mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13kg



UT4000 SERIES

Digital Storage Oscilloscope (Full Colour)

UT4102C • UT4152C • UT4202C



SPECIFICATIONS

NEW

Features	UT4102C	UT4152C	UT4202C
Bandwidth	100 MHz	150 MHz	200 MHz
Rise Time	≤3.5 ns	≤2.3 ns	≤1.8 ns
Sample Range		2GS/s	
Vertical Sensitivity		2mV ~ 5V/div	
Record Length (Max)		1024k	
Sample Rate		Real time 1GS/s, Equivalent: 25GS/s	
Scan Time Base	5ns ~ 50s/div	2ns ~ 50s/div	2ns ~ 50s/div
Trigger Type		Edge, Pulse, Video, Slope and Alternate	
Automatic Waveform Measurements		28	
Ports		Standard: USB Device, USB Host ; PASS/FAIL. Optional: LAN and GPIB	
Mathematics		Add, Subtract, Multiply, Divide, Reverse and FFT	
Applications		College Education, R&D, Electronic product assemble line, Industrial Control etc.	
Other Features		Digital Multimeter and Logic Analyzer	

GENERAL CHARACTERISTICS

Power	100 - 240VAC _{RMS} , 45Hz - 440Hz, CAT II
LCD Size	Diagonal: 145mm (5.7 inches)
Product Colour	Red and Grey, White and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm (wide) x 165mm (high) x 165mm (deep)
Standard Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe x 1, Multimeter Probe x 2, Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	480 x 440 x 300mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13kg



UT3000 SERIES

Digital Storage Oscilloscope (Full Colour / Monochrome)

UT3025B/C • UT3042B/C • UT3062B/C • UT3082B/C



SPECIFICATIONS

NEW

Features	UT3025B	UT3025C	UT3042B	UT3042C	UT3062B	UT3062C	UT3082B	UT3082C
Bandwidth	25 MHz		40 MHz		60 MHz		80 MHz	
Rise Time	≤14 ns		≤8.7 ns		≤5.8 ns		≤4.5 ns	
Sample Range	250MS/s				500MS/s			
Vertical Sensitivity	25M-40M Bandwidth : 2mV ~ 10V/div				60M-80M Bandwidth : 2mV ~ 5V/div			
Record Length (Max)					1024k			
Sample Rate	Real time: 250MS/s				Real time: 500MS/s, Equivalent: 25GS/s			
Scan Time Base	20ns ~ 50s/div		10ns ~ 50s/div		5ns ~ 50s/div		5ns ~ 50s/div	
Trigger Type	Edge, Pulse, Video and Alternate							
Automatic Waveform Measurements	28							
Ports	Standard: USB Device, USB Host, PASS/FAIL. Optional: LAN & GPIB							
Mathematics	Add, Subtract, Multiply, Divide, Reverse and FFT							
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.							
Display	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VAC _{RMS} , 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Colour	Red and Grey, White and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm (wide) x 150mm (high) x 292mm (deep)
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	440 x 380 x 550mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	15kg



UT3000 SERIES

Digital Storage Oscilloscope (Full Colour / Monochrome)

UT3102B/C • UT3152B/C • UT3202B/C



SPECIFICATIONS

NEW

Features	UT3102B	UT3102C	UT3152B	UT3152C	UT3202B	UT3202C
Bandwidth	100 MHz		150 MHz		200 MHz	
Rise Time	≤3.5 ns		≤2.3 ns		≤1.8 ns	
Sample Range			500MS/s			
Vertical Sensitivity			2mV ~ 5V/div			
Record Length (Max)			1024k			
Sample Rate			Real time: 500MS/s, Equivalent: 25GS/s			
Scan Time Base	5ns ~ 50s/div		2ns ~ 50s/div		2ns ~ 50s/div	
Trigger Type			Edge, Pulse, Video and Alternate			
Automatic Waveform Measurements			28			
Ports	Standard: USB Device, USB Host, PASS/FAIL Optional: LAN & GPIB					
Mathematics	Add, Subtract, Multiply, Divide, Reverse and FFT					
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.					
Display	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VAC _{RMS} , 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Colour	Red and Grey, White and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm (wide) x 150mm (high) x 292mm (deep)
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	440 x 380 x 550mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	15kg



UT2000 SERIES

Digital Storage Oscilloscope (Full Colour / Monochrome)

UT2025B/C • UT2042B/C • UT2062B/C • UT2082B/C



SPECIFICATIONS

NEW

Features	UT2025B	UT2025C	UT2042B	UT2042C	UT2062B	UT2062C	UT2082B	UT2082C
Bandwidth	25 MHz		40 MHz		60 MHz		80 MHz	
Rise Time	≤1.4 ns		≤8.7 ns		≤5.8 ns		≤4.5 ns	
Sample Range	250MS/s				500MS/s			
Vertical Sensitivity	25M-40M Bandwidth : 2mV ~ 10V/div				60M-80M Bandwidth : 2mV ~ 5V/div			
Record Length (Max)					1024k			
Sample Rate	Real time: 250MS/s		Real time: 500MS/s, Equivalent: 25GS/s					
Scan Time Base	20ns ~ 50s/div		10ns ~ 50s/div		5ns ~ 50s/div		5ns ~ 50s/div	
Trigger Type	Edge, Pulse, Video and Alternate							
Automatic Waveform Measurements	28							
Ports	Standard: USB Device, USB Host, PASS/FAIL. Optional: LAN							
Mathematics	Add, Subtract, Multiply, Divide, Reverse and FFT							
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.							
Display	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VAC _{RMS} , 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Colour	Red and Grey, White and Grey
Product Net Weight	2.5kg (Excluding packaging)
Product Size	320mm (wide) x 150mm (high) x 130mm (deep)
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	455 x 430 x 280mm (0.055 CBM Per Export Carton)
Standard Carton Gross Weight	11kg



UT2000 SERIES

Digital Storage Oscilloscope (Full Colour / Monochrome)

UT2102B/C • UT2152B/C • UT2202B/C



SPECIFICATIONS

NEW

Features	UT2102B	UT2102C	UT2152B	UT2152C	UT2202B	UT2202C
Bandwidth	100 MHz		150 MHz		200 MHz	
Rise Time	≤3.5 ns		≤2.3 ns		≤1.8 ns	
Sample Range			500MS/s			
Vertical Sensitivity			2mV ~ 5V/div			
Record Length (Max)			1024k			
Sample Rate			Real time: 500MS/s, Equivalent: 25GS/s			
Scan Time Base	5ns ~ 50s/div		2ns ~ 50s/div		2ns ~ 50s/div	
Trigger Type			Edge, Pulse, Video and Alternate			
Automatic Waveform Measurements			28			
Ports			Standard: USB Device, USB Host, PASS/FAIL. Optional: LAN			
Mathematics			Add, Subtract, Multiply, Divide, Reverse and FFT			
Applications			College Education, R&D, Electronic product assemble line, Industrial Control etc.			
Display	Monochrome LCD, 320 x 240	64k, Full colour LCD, 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD, 320 x 240	Monochrome LCD, 320 x 240	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VAC _{RMS} , 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Colour	Red and Grey, White and Grey
Product Net Weight	2.5kg (Excluding packaging)
Product Size	320mm (wide) x 150mm (high) x 130mm (deep)
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	455 x 430 x 280mm (0.055 CBM Per Export Carton)
Standard Carton Gross Weight	11kg

UNI-TREND GROUP LIMITED

Rm 901, 9/F, Nanyang Plaza, 57 Hung To Road, Kwun Tong,
Kowloon, Hong Kong
Tel : (852) 2950 9168 Fax : (852) 2950 9303
Email : info@uni-trend.com
<http://www.uni-trend.com>

UNI-TREND ELECTRONIC (SHANGHAI) LIMITED

Rm 15, 11/F, China Merchants Tower, No.161, Lujia Zui Dong Road,
Pu Dong New District, Shanghai City, China
Postal Code : 200 120
Tel : (86-21) 5878 3888 Fax : (86-21) 5878 7888
Email : infosh@uni-trend.com.cn
<http://www.uni-trend.com.cn>

UNI-TREND TECHNOLOGY (DONGGUAN) LIMITED

Dong Fang Da Dao, Bei Zha Dong Fang Industrial Development District,
Hu Men Town, Dong Guan City, Guang Dong Province, China
Postal Code : 523 925
Tel : (86-769) 8572 3888 Fax : (86-769) 8572 5888
Email : info@uni-trend.com.cn
<http://www.uni-trend.com.cn>

UNI-TREND TECHNOLOGY (CHENGDU) LIMITED

2nd Floor, Section C, Hui Yuan Di Er Chan Ye Yuan, No 76, Shu Xi Road,
Cheng Du City, Si Chuan Province, China
Postal Code : 610 091
Tel : (86-28) 8751 3888 Fax : (86-28) 8751 5888
Email : infocd@uni-trend.com.cn
<http://www.uni-trend.com.cn>