



■ UT25A



■ UT25B

SPECIFICATIONS

Specifications	Range	Best Accuracy	
		UT25A	UT25B
Model		UT25A	UT25B
Operating Voltage	90~120VAC	✓	✓
Working Frequency	47~63Hz	✓	✓
GFCI Test	About 6mA	✓	✓
Indications	Open Ground	✓	✓
	Open Neutral	✓	✓
	Open Hot	✓	✓
	Hot/NEU Reverse	✓	✓
	Hot/GND Reverse	✓	✓
	GFCI Testing In Progrss	✓	✓
	Hot On NEU With Hot Open	✓	✓
	Correct	✓	✓
Features			
Adjustable Sensitivity		✓	✓
Beeper Indication		✓	✓
Flashing LED light Indication		✓	✓
NCV Test			✓
Low Battery Indication		✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery(6F22)
Product Color	Red and Grey
Product Net Weight	Transmitter-110g
	Receiver-110g
Product Size	Transmitter-103mm×56mm×30mm
	Receiver-192mm×54mm×28mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	40PCS
Standard Carton Measurement	575mm×405mm×380mm(0.088CBM Per Standard Carton)
Standard Carton Gross Weight	15.8 kg