CPC-85FR - Cable and wire cutter for CU/AL



Cutting Range:	85mm
Length:	710mm
Output:	6.7 Tons
Weight:	12.5kg

Notes

- For copper, aluminium cable and telephone cable.
- The head can be easiy opened to allow the cutting of running cables
- NOT for armoured cable

CPC-85H - Cable and wire cutter for CU/AL





Notes:

- Two stage pumping action for rapid blade movement
- Head rotates 180°
- NOT for armoured cable

CPC-100H - Hydraulic cable cutter



Cutting Range:	Barb Cu Strand: 42mm Barb AL Strand: 46mm Telephone cable CCP:100mm Lead Sheathed Cable: 100mm Underground Cable: 75mm
Length:	560mm
Output:	7.5 Tons
Weight:	11kg

Features:

NOT for armoured cable

CPC-130H - Hydraulic cable cutter



Cutting Range:	Cu/AL: 130mm
Cutting Nange.	Gu/AL. 130111111
Length:	600mm
Output:	7 Tons
Weight:	13kg

Features:

- Bolt lock head
- NOT for armoured cable

CPC-105KH - Hydraulic cable cutter, scissor



Cutting Range:	105mm² Cu/AL
Lenght:	540mm
Output:	13.7 Tons
Weight:	10.50kg

Features:

NOT for armoured cable

CPC-120KH - Hydraulic cable cutter, scissor type blade



Cutting Range:	120mm² Cu/AL
Length:	620mm
Output:	13.7 Tons
Weight:	12.96kg

Features:

NOT for armoured cable

CPC-65A - Hydraulic cable cutter, scissor type blade



Cutting Range:	65mm² Cu/AL
Length:	600mm
Output:	6.7 Tons
Weight:	4.08kg

Features:

• NOT for armoured cable

CPC-85K - Hydraulic cable cutter



Cutting Range:	85mm² Cu/AL
Length:	600mm
Output:	6.7 Tons
Weight:	4.5kg

Features:

- NOT for armoured cable
- Metal Case included


CGG40 - Hydraulic cutting tool (hand-held)



Cutting Range:	40mm²
Length:	645mm
Weight:	5.88kg

Features:

- Carry bag included
- NOT for armoured cable





Crimping Range:	16mm² - 240mm²
Length:	460mm
Output:	12 Tons
Accessories:	Case and Dies
Weight:	4.5kg
Dies Included:	25mm, 35mm, 50mm, 70mm, 95mm, 120mm, 150mm, 185mm, 240mm

Features:

• Manual release

HP-240F - Hydraulic crimping tool (hand-held)



Crimping Range:	16mm² - 240mm²
Length:	380mm
Output:	5 Tons
Accessories:	Case and Dies
Weight:	3kg
RAM Stroke:	15mm
Dies Included:	16mm, 25mm, 35mm, 50mm, 70mm, 95mm, 120mm, 150mm, 185mm, 240mm

Features:

Auto pressure valve

HP-240 - Hydraulic crimping tool (hand-held)



Crimping Range:	16mm² - 240mm²
Length:	480mm
Output:	12 Tons
Accessories:	Case and Dies
Weight:	3.8kg
Weight: RAM Stroke:	3.8kg 18mm

Features:

Manual release

HP-300 - Hydraulic crimping tool (hand-held)



Crimping Range:	16mm² - 300mm²
Length:	480mm
Output:	12 Tons
Accessories:	Case and Dies
Weight:	3.9kg
RAM Stroke:	18mm
Dies Included:	16mm, 25mm, 35mm, 50mm, 70mm, 95mm, 120mm, 150mm, 185mm, 240mm, 300mm

Features:

Manual Release

CO-630A for use with CFP800 -

Hydraulic crimping tool head

Crimping Range:	150mm² - 630mm²
Output:	35 Tons/10000PSI working Pressure
Length:	360mm
Weight:	16.5kg
RAM Stroke:	25mm
Accessories:	Case and Dies
Dies included:	150mm, 185mm, 240mm, 300mm, 400mm, 500mm, 630mm

Features:

• Case Included



CRIMPING



Crimping Range:	50mm² - 400mm²
Length:	620mm
Output:	12 Tons
Weight:	6.5kg
RAM Stroke:	30mm
Dies Included:	50mm, 70mm, 95mm, 120mm, 150mm, 240mm, 300mm, 400mm

Features:

• Twist release



Crimping Range:	50mm² - 400mm²
Length:	650mm
Output:	13 Tons
Weight:	7.2kg
RAM Stroke:	38mm
Dies included:	50mm, 70mm, 95mm, 120mm, 150mm, 185mm, 240mm, 300mm, 400mm

Features:

Twist Release

CYO-430H for use with CFP800 -

Hydraulic crimping tool head



Crimping Range:	50mm² - 400mm²
Output:	12 Tons
Weight:	4kg
Length:	340mm
RAM Stroke:	30mm
Accessories:	Case and Dies
Dies included:	50mm, 70mm, 95mm, 120mm, 150mm, 185mm, 240mm, 300mm, 400mm

Features:

Case included

CYO-510H - Hydraulic crimping tool head



Crimping Range:	50mm² - 400mm²
Length:	340mm
Output:	13 Tons
Weight:	5kg
RAM Stroke:	38mm
Dies Included:	50mm, 70mm, 95mm, 120mm, 150mm, 240mm, 300mm, 400mm

Features:

Case included



Crimping Range:	10mm² - 500mm² CU/AL
Length:	650mm
Output:	50kN
Weight:	4.3kg

Features:

Auto release

MAP-8W - Hydraulic hole punch 360° adjustable head for punching holes in electrical switchboards and panels



Max Thickness:	Mild Steel: 3.2mm² Staninless steel: 1.6mm²
Punching Force:	8.9 Tons
Dies Included:	21.8mm, 22.6mm, 54.1mm, 42.7mm, 48.7mm, 60.2mm

Notes:

- · Includes plastic carry case
- It contain hydraulic punch driver, with 360 degree rotatable head for flexible operation in place.
- With the help of hydraulic system, making holes by hand become fast and easy

MAP-8RA - Hydraulic hole punch with extended head 360° adjustable for punching holes in electrical switchboards and panels



Max Thickness:	Mild Steel: 3.2mm² Stainless Steel: 16mm²
Punching Force:	16 Tons
Dies Included:	21.8mm, 22.6mm, 54.1mm, 42.7mm, 48.7mm, 60.2mm

Notes:

Includes plastic carry case

MAP-8A - Inline hydraulic hole punch 360° adjustable for punching holes in electrical switchboards and panels



Max Thickness:	Mild Steel: 3.2mm² Staninless steel: 1.6mm²
Punching Force:	16 Tons
Dies Included:	21.8mm, 22.6mm, 54.1mm, 42.7mm,
	48.7mm, 60.2mm

Notes:

- Includes plastic carry case
- It contain hydraulic punch driver.
- With straight head, compact and easy carrying.
- With the help of hydraulic system, making holes by hand become fast & easy
- 360 degree head design for flexible operation in place.

MAP-8ZA- Hydraulic hole punch with swivel head (90° Head) for punching holes in electrical switchboards and panels



Max Thickness:	Mild Steel: 3.2mm² Staninless steel: 1.6mm²
Punching Force:	8.9 Tons
Dies Included:	21.8mm, 22.6mm, 54.1mm, 42.7mm, 48.7mm, 60.2mm

Notes:

• Includes plastic carry case

SYK-15 - Compact, light and fast hydraulic hole punch 360° adjustable for punching holes in electrical switchboards and panels

Punching Range:	Mild Steel: below 3mm (Ø 16.5 - 115.5mm) Staninless steel: 1.6mm ²
Punching Force:	15 Tons
Dies Included:	Round Punch: Ø 220mm, 27.5mm, 34.3mm, 43.0mm, 60.8mm, up to 115.5mm Square Punch: 32.0 x 32.0mm

Notes:

- Small rod, large rod and O-ring set
- Includes plastic carry case



FOOT PUMP

CFP-800 - Foot operated, 2 stage, hydraulic pump complete with hose and female coupling

Pressure:	700 Bar 10 000psi
Weight:	17.7kg

Features:

- Single-acting foot pump
- With pressure release lever with wide bottom frame
- High pressure oil pipe supplied
- Foot operated style
- Quick couple kept fast connection with compatible tools
- Double speed unit: for quick operation, allow quick oil delivery under no load condition (12.26cc/stroke) and then build sufficient working pressure under load condition (20-700 bar)
- · Safety valve: automatically relieves pressure when rated pressure is reached, to protect hydraulic system from over pressure
- Packed with steel case packing for easy carrying and protect pumps well during shipping



BATTERY OPERATED TOOLS

CRIMPING

BPL55OA1120 - Inline Hydraulic crimping tool, battery operated hand grip crimping tool



Crimping Range:	6mm² - 240mm² CU/AL
Weight:	2.9kg
Battery:	18V
Length:	128mm
Accessories:	Case and Charger
Dies Available:	6/35; 10/50; 16/70; 25/95; 4/120; 150; 185; 240

Features:

- Robust plastic housing with rubber grip handle Quick opening and closing head, 180° rotatable with interchangeables dies and wide crimping
- Maximum operating speed with high performance motor
- Quick motor stop function for high user safety
- Simple display panel with light diode for battery charge level, crimping failure and maintenance control
- Manual retraction when crimp is complete
- Large and ergonomics triggers
- Pressure safety system to prevent over pressure failures
- Energy saving function by stopping tool after 10 min unused USB connection for data analysis & preventive maintenance with dedicate
- Workplace illumination by LED

BPL62OA1120 - Inline hydraulic crimping tool, battery operated hand grip crimping tool



Crimping F	Range:	6mm² - 300mm² CU/AL	
Weight:		2.9kg	
Battery:		18V	
Length:		128mm	
Accessorie	es:	Case and Charger	
Dies availa	able:	6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300	

Features:

- Robust plastic housing with rubber grip handle
 Quick opening and closing head, 180° rotatable with interchangeables dies and wide crimping
- Maximum operating speed with high performance motor
- · Quick motor stop function for high user safety
- Simple display panel with light diode for battery charge level, crimping failure and maintenance control
- Manual retraction when crimp is complete
- Large and ergonomics triggers
- Pressure safety system to prevent over pressure failures
- Energy saving function by stopping tool after 10 min unused USB connection for data analysis & preventive maintenance with dedicate
- Workplace illumination by LED