

UNI-T®

IT'S ALL ABOUT THE QUALITY

FROSTY

SPECIALS

THREE-D
AGENCIES
THE CABLE ACCESSORY COMPANY

Promotion runs from 1 May 2025 to 31 August 2025 or while stocks last. E & OE. www.uni-trend.co.za

UTi260B THERMAL IMAGER

- IR Resolution: 256 x 192 Pixels
- Display: 2.8" LCD
- Temperature Range: -15°C ~ 550°C
- Palettes: Iron, Rainbow, Grey
- NETD: ≤ 50mK
- Display Mode: Thermal; Visible; Blending
- Spatial Resolution: 3.8mrad
- Frame Rate: <25Hz
- PC Analysis Software
- FOV: 56°(h) * 42°(v)
- High and Low Temperature Tracking
- Photograph Function with SD Card Storage
- PC Analysis Software
- Buzzer/Flashlight Alarm
- Real-time Capture of Hi/Low Temperature
- Flashlight
- Tripod Mounting Hole



Excl VAT
R8 647.00

UT33D+ PALM SIZE MULTIMETER

- AC/DC Voltage: 600 V
- DC Current: 10A
- Resistance: 20MΩ
- NCV • APO
- Diode
- Continuity Buzzer
- LCD Backlight
- Relative Mode
- LCD Size 53mm x 28mm
- Probe Placing Slots
- 2000 Display Count



Excl VAT
R289.00

UT216C TRMS CLAMP METER

- AC/DC Current: 600A
- DC Voltage: 1000V
- Capacitance: 60mF
- Temperature: -40°C ~ 1000°C
- Auto Ranging
- NCV
- Flashlight
- MAX/MIN/REL
- Continuity Buzzer
- Input Protection
- Ideal for Solar Power Systems
- Inrush Current
- 6000 Display Count



Excl VAT
R2 871.00

UT200B+ CLAMP METER

- AC Current: 600A
- DC Voltage: 600 V
- AC Voltage: 600V
- Frequency: 10H ~ 10kHz
- Resistance: 30kΩ
- Capacitance: 300μF
- Auto Range
- Jaw Capacity 28mm
- Diode • Continuity Buzzer
- Low Battery Indication
- Data Hold • LCD Backlight
- Flashlight
- High Voltage Warning
- 3099 Display Count



Excl VAT
R541.00

UT121A SMART DIGITAL MULTIMETERS

- AC/DC Voltage: 600V
- Temperature: -40°C ~ 1000°C
- Dual Display
- NCV
- Diode
- LCD High Voltage Alert
- Low Battery Indication
- Data Hold
- Resistance: 10MΩ
- Auto Range
- LIVE Detection
- Continuity
- Flashlight
- APO
- Display Count 6099



Excl VAT
R422.00

UT219DS PROFESSIONAL TRMS CLAMP METER

- AC/DC Current: 600A
- LoZ ACV: 600V
- Capacitance: 60mF
- Temperature: 1000°C
- Motor 3 Phase Test 80VAC ~ 600VAC
- Motor Phase Sequence Measurement With 2 Probes
- AC+DC Dual-mode Display (V+I)
- Diode
- APO
- Data hold
- Zero Hold
- Relative Mode
- Auto/Manual Ranging
- Low Battery Indication
- Auto Backlight
- AC/DC Voltage: 1000 V
- Resistance: 60MΩ
- Frequency: 40MHz
- Diode
- Duty Cycle
- Inrush Current
- Low Pass Filter
- Flashlight
- Jaw Size: 33mm
- Sampling Rate: 5 times/sec
- V + A Dual Display
- 6000 Display Count



Excl VAT
R4 306.00

UT201+ 400A TRMS CLAMP METER

- AC Current: 400A
- AC/DC Voltage: 600V
- Resistance 40MΩ
- Display Size: 35 x 27mm
- Backlight
- NCV
- MAX/MIN
- Auto Ranging
- Data Hold
- Diode
- Continuity Test
- Low Voltage Indicator
- Jaw Capacity 28mm
- APO
- 4000 Display Count



Excl VAT
R658.00

UT205E TRMS CLAMP METER

- AC Current: 1000A
- AC/DC Voltage: 1000 V
- Resistance: 60MΩ
- Capacitance: 60mF
- Temperature: -40°C ~ 1000°C
- Auto/Manual Range
- Jaw Capacity 42mm
- Diode • Data Hold
- APO • MAX/MIN/REL
- LCD Backlight
- Flashlight • Continuity Buzzer
- NCV • Low Battery Indication
- 6000 Display Count



Excl VAT
R1 383.00

UT206A+ TRMS CLAMP METER

- AC Current: 1000A
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 45Hz ~ 1kHz
- Temperature: -40°C ~ 1000°C
- Jaw Capacity > 40mm
- Inrush Current: 1000A
- Auto Range
- Diode
- NCV
- Data Hold
- MAX/MIN/REL
- LCD Backlight
- Continuity Buzzer
- APO
- Low Battery Indication
- 6000 Display Count



Excl VAT
R1 422.00

UT203+ 400A TRMS CLAMP METER

- AC/DC Current: 40/400A
- AC/DC Voltage: 600V
- Resistance: 40MΩ
- Capacitance: 10mF
- Frequency: 10MHz
- Duty Cycle
- Diode Test
- Continuity Buzzer
- Data Hold
- Low Battery Indication
- Jaw Capacity 28mm
- Relative Mode
- MAX/MIN
- Display Size: 35 x 27mm
- 4000 Display Count
- NCV
- APO
- Backlight
- Auto Range



Excl VAT
R1 354.00

UT18E VOLTAGE AND CONTINUITY TESTER

- AC/DC Voltage Display (V) 6V ~ 1000V
- Phase Rotation Test
- Continuity Test: Resistance 0~100kΩ, Beeper LED Light Indicator
- Self-inspection
- Polarity Detection
- Low Battery Indication
- RCD Test
- No Power Test
- Auto Range
- Over Voltage Protection



Excl VAT
R1 324.00

UT125C POCKET SIZE MULTIMETER

- AC/DC Voltage: 600V
- AC/DC Current: 400mA
- Resistance: 40MΩ
- Frequency: 60kHz
- Capacitance: 100μF
- Diode
- Continuity Buzzer
- NCV
- Low Battery Indication
- Data Hold
- APO
- Duty Cycle Measurement
- 4000 Display Count



Excl VAT
R609.00

UT12D DUAL AC VOLTAGE DETECTOR

- AC Voltage: 90V~1000V
- Sensitivity Switching: Auto
- Flashlight
- Neutral & Live Line Distinction
- AC Voltage: 24V~1000V
- APO
- Audible/Visual Alarm
- Indication LED: Green/Red /Yellow



Excl VAT
R160.00

UT677A BATTERY INTERNAL RESISTANCE TESTER

- Battery Internal Resistance Range: 0.0mΩ ~ 3mΩ
- Batter Voltage Range: 0.0V ~ 71V
- Temperature Range: -10°C ~ 60°C
- Screen: 3.5 inches
- Response Time: 200ms
- Measuring Time: 2sec
- USB Interface
- Data hold and Storage
- Measurement Judgement Function
- APO
- Bluetooth



Excl VAT
R8 500.00

UT133B MULTIMETER

- AC/DC Voltage: 600 V
- DC Current: 10A
- Resistance: 60MΩ
- Capacitance: 9.9999mF
- APO
- Diode
- Continuity Buzzer
- Low Battery Indication
- Data Hold
- Overload Indication
- Test Probe Holder
- LCD Backlight
- Battery Test 15 & 9V
- NCV
- 6000 Display Count



Excl VAT
R588.00

UT136B+ MULTIMETER

- AC/DC Voltage: 1000 V
- AC/DC Current: 10A
- Resistance: 40MΩ
- Capacitance: 40mF
- Frequency: 400Hz ~ 40MHz
- APO • Data Hold
- hFE Transistor Test
- Diode • NCV
- Low Battery Indication
- Overload Alarm
- Continuity Buzzer
- LCD Backlight
- 4000 Display Count



Excl VAT
R613.00

UT33C+ PALM SIZE MULTIMETER

- AC/DC Voltage: 600 V
- DC Current: 10A
- Resistance: 20MΩ
- Temperature: 1000°C
- APO • Diode
- Continuity Buzzer
- LCD Backlight
- Relative Mode
- LCD Size 53mm x 28mm
- Probe Placing Slots
- 2000 Display Count



Excl VAT
R341.00

UT123D POCKET SIZE HOUSEHOLD TRUE RMS MULTIMETER

- AC/DC Voltage: 600V
- AC/DC Current: 10A
- Resistance: 40MΩ
- Capacitance: 400μF
- Acousto-optic Indication
- Data Hold
- APO
- Low Battery Indication
- NCV/Live
- 4000 Display Count



Excl VAT
R578.00

a member of the **Hudaco** group

Promotion runs from 1 May 2025 to 31 August 2025 or while stocks last. E & OE. www.uni-trend.co.za

UT61D+ TRMS MULTIMETER

- AC/DC Voltage: 1000 V
- AC/DC Current: 20A
- Resistance: 60MΩ
- Frequency: 10Hz ~ 10MHz
- Capacitance: 60mF
- Temperature: -40°C ~ 1000°C
- MAX/MIN
- Continuity Buzzer
- Relative Mode
- NCV
- Data Hold
- LoZ ACV
- LCD Backlight
- Low Battery Indication
- Auto Power Off
- Display Count 6000
- USB Connections
- Diode
- Analog Bar
- Auto Range
- Peak Hold

Excl VAT
R1 543.00

UT320T MINI DUAL CONTACT THERMOMETER

- Measurement Range: -40° ~ 300°C
- Distance To Spot: 8:1
- Emissivity: Adjustable
- Spectral Range: 5µm ~14µm
- Class 2 Laser
- Probe Measurement: -40°C ~300°C
- Probe Type: NTC
- Minimum Measuring depth: 12.7mm
- Data Hold
- Lock Measurement
- MAX/MIN/DIFF

Excl VAT
R1 127.00

UT516B INSULATION RESISTANCE METER

- 5KV Digital Insulation Resistance Tester
- Insulation Resistance up to 1000GΩ
- 1000V AC/DC
- Data Logging 18
- APO
- Polarization Index (Pi)
- USB Interface
- LCD Backlight
- Over-Range Warning
- Comparison Measurement
- Low Battery Indication
- 10 000 Display Count

Excl VAT
R30 663.00

UT501A 5.5GΩ INSULATION RESISTANCE TESTER

- Test Voltage 100/250/500/1000V
- Insulation Resistance (Ω) 5.5GΩ
- Short Circuit Current: <2mA
- AC Voltage (V) 750V
- Auto Range
- Low Battery Indication
- LCD Backlight
- Alarm Indication
- Alarm Buzzer
- High Voltage Indication
- Overload Indication
- Auto Discharge
- 10mΩ Internal Resistance Test
- 2000 Display Count

Excl VAT
R1 649.00

UT363BT MINI ANEMOMETER

- Wind Speed Rate: 0 ~ 30m/s
- Temperature Range: -10°C ~ 50°C
- Beaufort Wind Scale 0~12 level
- Wind Speed Resolution 0.1m/s
- Temperature Resolution 0.1°C
- Sampling Rate 0.5/s
- APP
- Bluetooth App
- Data Hold
- APO
- Low Battery Indication
- MAX/AVG Mode
- LCD Backlight
- Overload Indication
- Wind Speed Unit Selection: m/s, km/h, ft/min, knots, mph
- Temperature °C/°F

Excl VAT
R596.00

UTX325 THERMAL IMAGING MONOCULAR

- Display: 0.4" LCOS
- IR Resolution: 384 x 288
- Pixel Size: 12µm
- Thermal Sensitivity: <40mK
- Lens Focal Length: 25mm
- Diopter Adjustment: -4D ~+5D
- Colour Palettes: Black Hot, White Hot, Hottest, Ironbow, Rainbow
- Calibration Modes: Auto, Manual, Background
- Detector Type: UFPA
- Spectral Range: 8 ~14µm
- Frame Rate: <50Hz
- Focus: Manual Focus
- Field of View: 10.5° (H) x 7.9° (V)
- Digital Zoom: 2x; 4x
- Hot Trace

Excl VAT
R20 050.00

UT353BT MINI SOUND LEVEL METER

- Range: 30dB ~ 130dB
- Accuracy: +/- 1.5dB
- Frequency Response: 31.5Hz ~ 8kHz
- Resolution 0.1dB
- Sampling Rate: Fast: 125ms, Slow: 1000ms
- Bluetooth App
- Bluetooth
- Data Hold
- APO
- MAX/MIN
- Low Battery Indication
- LCD Backlight
- Overload Indication

Excl VAT
R643.00

UT383S MINI LIGHT METER

- Illuminance Measurement (Lux): 0 ~ 199,900 Lux
- Illuminance Measurement (FC): 0 ~ 18,500FC
- Data Hold
- APO
- MAX/MIN
- LCD Backlight
- Overload Indication
- Unit Selection
- Split Design

Excl VAT
R927.00

LM1000 RANGE FINDER

- Distance Range: 1m - 900m
- Height: 400m
- Accuracy: 0.2%
- Velocity Range: 0-300km/h
- Magnification: 7x
- Power: 3.7V Li-ion
- Angle: +/- 60°
- Pulse Laser (Harmless to Eyes)
- Fast Distance Measurement
- APO
- LCD Display

Excl VAT
R2 665.00

UT302D+ INFRARED THERMOMETER

- Dual Laser
- Temperature: -32°C ~1100°C
- Accuracy: +/- 1.5°C
- D:S Ratio: 20:1
- Emissivity: 0.1 ~ 1.0 Adjustable
- High/Low Temperature Alarm
- Audible Alarm
- MAX/MIN Measurement
- Data Storage 99
- Scheduled Measurement
- Date/Time
- High Contrast Colour EBTN Display

Excl VAT
R1 741.00

UT320D MINI DUAL CONTACT THERMOMETER

- Measurement Range: -50 ~ 1300°C
- Dual Display Mode T1 & T2
- Difference Measurement T1 - T2
- MAX/MIN/AVG
- Backlight
- Data Hold
- APO
- Low Battery Indication
- Selection °C/°F
- Dual Thermocouples
- Mode Selection K/J

Excl VAT
R526.00

UTX318M THERMAL MONOCULAR 18MM WITH WIFI

- Display: 0.39"OLED
- IR Resolution: 400 x 300
- Pixel Size: 12µm
- Thermal Sensitivity: <25mK NETD
- Lens Focal Length: 18mm
- Eyepiece Relief Distance: 18mm
- Colour Palettes: Black Hot, White Hot, Hottest, Ironbow, Rainbow
- Digital Zoom: 2x; 4x; 8x
- Scene Modes: Bird, Forest, Rock
- Calibration Modes: Auto, Manual, Background
- Stadiametric Ranging
- PIP
- Video Recording
- Wi-Fi
- Detector Type: UFPA
- Spectral Range: 8 ~18µm
- Frame Rate: <50Hz
- Focus: Manual Focus
- Field of View: 14.6° (H) x 11° (V)
- Diopter Adjustment: -4D ~+5D
- Smart Standby
- E-Compass
- Hot Trace
- IP67
- 2m Drop
- 16GB Internal Storage

UT306C INFRARED THERMOMETER

- Circle Laser
- Temperature: -50°C ~500°C
- Accuracy: +/- 2°C
- D:S Ratio: 12:1
- EBTN Display
- Emissivity: 0.1 ~ 1.0 Adjustable
- °C/°F Selection
- High/Low Temperature Alarm
- Laser On/Off
- APO
- Low Battery Indication
- MAX/MIN/AVG/DIFF Modes
- Response Time: 500s
- Data Hold

Excl VAT
R470.00

UT372D 2-IN-1 TACHOMETER

- **Non-contact Measurement:**
- RPM Range: 1RPM ~ 99,99RPM
- Frequency: 1 ~ 1.66Hz
- Count: 1 ~ 99,99REV
- Target Distance: 50mm ~ 500mm
- **Contact Measurement:**
- RPM Range: 1 ~ 19,99RPM
- Frequency: 1 ~ 333Hz
- Surface Velocity: 6 ~ 60in/min
- Length: 0 ~ 99999 (m/ft/in)
- Measurement More: Contact RPM / Non-contact RPM / Counting / Frequency / Surface Velocity / Length
- Statistical Measurement: Max / Min / Last Reading / Ave
- Data Storage (10)
- APO

Excl VAT
R2 447.00

UT22B-EU VOLTAGE AND CONTINUITY TESTER

- Voltage Indicaion (V AC/DC): 6V ~ 400V
- Frequency: 50/60Hz
- Auto Detection of AC/DC
- Voltage Indication
- Input Protection

Excl VAT
R374.00

UT300S 400°C INFRARED THERMOMETER

- Temperature: -32 ~ 400°C
- Accuracy +/- 2°C
- Distance To Spot Ratio: 12:1
- Response Time 500ms
- Emissivity 0.10 ~ 1.00 Adjustable
- Selection °C/°F
- Display Hold
- APO
- Low Battery Indication
- MAX/MIN
- High Alarm
- Low Alarm
- LCD Backlight
- Auto Data Hold
- Optional (on/off) Laser Pointer
- Single Laser

Excl VAT
R420.00

UT673A BATTERY TESTER

- 12V Battery Test: 7 ~ 16V DC
- 12V/24V Cranking System Test: 7 ~ 30V DC
- 12V/24V Charging system test: 7 ~ 30V DC
- Battery Type: Ordinary Lead Acid Battery, AGM Flat Plate Battery, AGM Spiral Battery, GEL Battery, EFB Battery
- Battery Capacity: 3 ~ 250Ah
- Over Voltage Protection
- Reverse Connection Protection
- A Prompt For Poor Contact
- Battery Status, Life, Capacity Display
- Battery Internal Resistance Display
- Four-Termina Kelvin Test
- Test without Battery Disassembly
- LED Colour Indication for Test Results

Excl VAT
R1 051.00

LM555LD LASER LEVELER

- Display Type: Green LD
- Line Type: 4V1H 1D
- Laser Wavelength: 510 ~ 515nm
- Light Source: < 1mW
- Laser Class: 2
- Expanded Angle: H130° / V 110°
- H/V Accuracy: +/- 3.5°
- Self-Leveling Method: Gravity Pendulum Magnetic Damping
- Self-Leveling Time: <3s
- Working Distance: Line 20m, Point 25m@200Lux
- Working Time: >5h (All Lasers On)

Excl VAT
R3 310.00

UT-C01 HOOK TYPE TEST CLAMP

- Rod Length: 6.2mm can extend to 7.5mm
- Safety Handle and Spri

Excl VAT
R76.00



- UT387D
WALL SCANNER**
- Detect Principle: Electro-Magnetic Induction
 - Detects Wooden Beams, Metal Objects, Electrical Wire
 - Metals Scan Depth: 100mm - Iron Pipe 80mm - Brass Pipe
 - Stud-scan Depth (Wood): 38mm
 - Thick-scan Depth (Wood): 50mm
 - AC Electrical Wire Depth: 50mm
 - Voice Notification
 - APO
 - Low Battery Indication

Excl VAT
R1 405.00

**UT343D COATING
THICKNESS GAUGE**

- Measuring Range: 0 ~ 1250µm
- Accuracy: 1µm
- Resolution: 0.1µm
- Measurement Method: Single/Continuous
- Metal Type: Ferrous / Non-Ferrous
- Display Type: 2.0 inches TFT LCD (320 x 240)
- LCD Brightness Control
- Auto Rotatable Screen
- Unit Conversion
- Audio Alarm
- LED Alarm
- PC Analysis Software
- USB Communication
- Quick Test Mode
- Data Storage 500
- APO
- Low Battery Indication



Excl VAT
R2 706.00

**UT261A PHASE SEQUENCE &
MOTOR ROTATION INDICATOR**



- AC Voltage: 40V ~ 690V
- Frequency: 15Hz ~ 400Hz
- Working Current: < 1mA
- Phase Sequence Indication: LCD
- Missing Phase Indication: LCD
- No Batteries Required

Excl VAT
R1 392.00

**UTP1310
POWER SUPPLY**

- Output Voltage: 32V
- Output Current: 10A
- Output Power: 320W
- Resolution: 10mV / 1mA
- Panel lock function
- Over Current Protection



Excl VAT
R3 125.00

**UT311A VIBRATION
TESTER**

- Acceleration (PEAK): 0.1 ~ 199.99m/s²
- Datahold
- Velocity (RMS): 0.1 ~ 199.9mm/s
- Flashlight
- Displacement: 0.0001 ~ 1.99mm
- LCD Backlight
- Automatically Rotatable Screen
- APO
- High/Low Frequency Acceleration
- Long and short Probes
- Battery Indication
- USB-C Changing Interface



Excl VAT
R8 213.00

UT658A USB TESTER

- Input & Output Ports: USB Type A
- Voltage Range: 4 ~ 24VDC
- Current Range: 0.05 ~ 3ADC
- Capacity: 0 ~ 99999mAh
- Energy: 0 ~ 1000Wh
- Circuit Equivalent Resistance Measurement: 1 ~ 480Ω
- USB Data Cable Voltage (D+, D-): 0 ~ 3.3V
- Maximum Recording Time: 99h, 59min, 59sec
- Fast Charge Protocol: Type A: Supports USB 2.0 Data Transmission & QC1.0/2.0/3.0 Fast Charge Protocol



Excl VAT
R212.00

**UT682D
WIRE TRACKER**

- Wire Types: Telephone Lines/Twisted Pair/Electric Wire
- Telephone Wire Test Distance ≥3000m
- Polarity Indication for Phone Lines
- Transmitter Output Voltage: 8V DC
- Transmitter Power Supply: 9V Battery
- Receiver Power Supply: 9V Battery
- Polarity Indication for Telephone Wires
- Max Receiver Operating Current 40mA
- Max Receiver Standby Current 10mA



Excl VAT
R584.00

**A12T TEMPERATURE
HUMIDITY METER**

- Temperature: -10 ~ 50°C
- Sampling Time: 10s
- Display of Temperature, Humidity and Time
- Dual Temperature Measurement
- Humidity: 20% ~ 95% RH
- External Temperature: -10°C ~ 50°C
- MAX/MIN
- Comfort Rating: Cold/Dry/Comfort
- Alarm Clock/Time Display
- 12/24 Hour Mode



Excl VAT
R305.00

UT-C02A ALLIGATOR CLIPS

- Through Hole Alligator Clip
- Length: 80mm
- Clip Opening: 36mm
- CAT Rating: CATIII 1000V, CAT IV 600V 10A
- Recommended Test Leads: UT-L13



Excl VAT
R198.00

**UT-L13
DOUBLE INSULATED
TEST LEADS**

- Cable Length: 900mm
- Standard Banana Interface: Ø4mm
- Body Length: 128mm
- Probe Length: 18mm
- CAT Rating: CATIII 1000V 10A
- Recommended Alligator Clips: UT-C02A / UT-C04A
- Double Insulation
- UL Authenticated
- Removable Insulation Cap



Excl VAT
R212.00

**UT219P AC DIGITAL
POWER CLAMP
METER**

- AC Current: 1000A
- AC Voltage: 1000 V
- Power (Single Phase): 1000KW
- Power (3 Phase & 3 Wires): 1732KW
- Power (3Phase & 4 Wires): 3000KW
- Power Factor: -1 ~ 1
- Power Frequency: 15Hz ~ 1000Hz
- Jaw Opening 75mm
- Phase Detection: Positive & Negative
- AC/DC PEAK Measurement: 32 times
- LCD Screen
- APO
- Bluetooth
- Data hold
- True RMS
- Overload Indication
- High Voltage Indication
- High Voltage Overload Warning
- Low Battery Indication
- 9999 Display Count



Excl VAT
R7 068.00

**UT71E
INTELLIGENT
TRMS MULTIMETER**

- AC/DC Voltage: 1000V
- AC/DC Current: 10A
- Resistance: 40MΩ
- Frequency: 40Hz ~ 400MHz
- Capacitance: 40mF
- Temperature: -40°C ~ 1000°C
- Power Measurement: 2500W
- AC & DC Dual Display
- Loop Test: 4 ~ 20mA
- Bluetooth & USB Interface
- Diode
- APO
- Continuity Buzzer
- Low Battery Indication
- Data Logging 10000
- MAX/MIN/REL
- K-Type Temp Probe
- Smart Phone APP
- 40 000 Display Count



Excl VAT
R2 900.00

**UT120B POCKET SIZE
MULTIMETER**

- AC/DC Voltage: 600V
- Resistance: 40MΩ
- Capacitance: 100µF
- Frequency: 10MHz
- Duty Cycle
- Data Hold
- APO
- Diode
- Continuity Buzzer
- Low Battery Indication
- Relative Mode
- 4000 Display Count



**LM570LD-II LASER
LEVELER**

- Laser Type: Green LD
- Laser Line: 2 Lines
- Operating Distance: 10m
- Laser Wavelength: 520nm
- Laser Class: 2
- Laser Accuracy: +/-3mm/10m
- Self-Leveling Range: +/- 3°
- Self-Leveling Time: < 3s
- Working Hours: > 4h



Excl VAT
R1 310.00

**LM600
GOLF RANGE FINDER**

- Distance Range: 3m ~ 600m
- Height: 250m
- Speed Range: 0 ~ 300km/h
- Magnification: 6x
- Angle: +/- 60°
- Eye Piece Aperture: 15mm
- Exit Pupil Diameter: 3.7mm
- Flagpole Lock
- Slope Measurement
- APO
- Accuracy: 0.2%
- Power: 3.7V Li-ion
- Objective Aperture: 19mm
- Golf Trajectory Compensation Mode
- Height Measurement



Excl VAT
R1 861.00

UT522 EARTH GROUND TESTER

- Earth Resistance: 0 ~ 4000Ω
- AC Earth Voltage: 0 ~ 400V
- Manual Range • APO
- Low Battery Indication
- Data Hold • Data Storage 20
- LCD Backlight • Full Icon Display
- Double Insulation Protection
- Contact Badness Indication
- Simple 2-Wire Testing
- Precision 3-Wire Testing
- Over-Range Display
- 4000 Display Count



Excl VAT
R4 900.00

UT256B OPEN JAW TRMS CLAMP METER

- AC/DC Current: 200A
- DC Voltage: 1000 V
- AC Voltage: 750V
- Resistance: 60MΩ
- Capacitance: 60mF
- Auto Ranging
- Diode • NCV
- Data Hold • Zero Mode
- LCD Backlight
- APO
- Continuity Buzzer
- Input Protection
- Low Battery Indication
- Relative Mode
- 6000 Display Count

Excl VAT
R1 974.00



Excl VAT
R5 460.00

UT533 TRMS INSULATION RESISTANCE MULTIMETER

- 1000V AC/DC
- Capacitance 100μF
- Frequency 1MHz
- Temperature -40 ~ 537°C
- Resistance 40MΩ
- Short Circuit Current: < 2mA
- Diode Test
- Auto Range
- APO
- Data Logging 99
- Insulation Resistance (50/100/250/500/1000V)
- Continuity Buzzer
- Low Battery Indication
- Data Hold
- LCD Backlight
- 6000 Display Count

UT278C GROUND PILE CLAMP EARTH RESISTANCE TESTER

- Ground Resistance: 0 ~ 1800Ω
- Leakage Current: 50A
- Current Resolution: 1uA
- Soil Resistivity: 0 ~ 9999kΩ
- Ground Voltage: 600V
- Jaw Size: 68mm
- USB Data Upload
- Data Storage (500)
- Overload Indication
- Backlight • APO
- Alarm Function
- Overload Protection

Excl VAT
R14 252.00



OTHER PRODUCTS

M30 HANDHELD THERMOGRAPHY CAMERA

- Thermal resolution: 384 x 288 (110 592 pixels)
- NETD : < 35mK
- Temperature measurement range : -20 °C ~ 550 °C
- Accuracy: Max (±2°C ±2%),
- Measurement Presets: Center spot, Hot spot, Cold spot,
- User Preset Point/Line/Area
- FOV: 37.5° x 28.5°
- Pixel Pitch: 17μm
- Colour Palettes: White Hot, Black Hot, Rainbow, Ironbow, Red hot, Fusion, Rain
- Manual focus
- Image Mode: Thermal / Optical / Fusion / PIP
- 25 Hz image frequency
- 3.5" LCD touch screen display
- Bluetooth • WiFi
- USB Interface
- www.hikmicrotech.com/en/download/5



Excl VAT
R40 031.00

MINI2PLUS THERMAL IMAGING CAMERA ADAPTOR FOR ANDROID

- Infrared Image:**
- IR resolution: 256 x 192 (49,152 pixels)
- NETD : < 40mK
- Image Frequency: 25Hz
- Field of View: 25° x 18.8°
- Manual Focus
- Measurement & Analysis**
- Object Temperature Range: -20°C ~ 350°C
- Accuracy: Max (+/-2°C)
- Measurement Tools: Center Spot, Hot Spot, Cold Spot, User-Definable: 3 Spots and 3 Rectangles
- General:**
- Portable
- Android Smartphone and Tablet
- Weight: Approx. 20g
- USB Interface USB-C



Excl VAT
R4 911.00

BX20 HANDHELD THERMAL IMAGING CAMERA

- Infrared Image:**
- IR resolution: 256 x 192 (49,152 pixels)
- SuperIR: 320 x 240 (76,800 pixels)
- NETD : < 40mK
- Image Frequency: 25Hz
- Field of View: 50° x 37.2°
- Spatial Resolution: 3.3mrad
- Focus Mode: Focus Free
- Image Display:**
- Visual Camera: 1600 x 1200 (2MP)
- Image Modes: Thermal / Fusion / Visual / PIP
- Palettes: White Hot, Black Hot, Rainbow, Ironbow
- Display: 240 x 320 Resolution, 3.2" LCD Screen
- Measurement & Analysis**
- Min. Focusing Distance: 0.3m
- Object Temperature Range: -20°C ~ 550°C
- Accuracy: Max (+/-2°C)
- Data Storage & Communication:**
- Storage Media: Built-in 16 GB Flash Memory
- File Format: Radiometric JPEG
- Storage Capacity: Up to 90,000 images
- General:**
- Wi-Fi: 802.11b/g/n (2.4GHz)
- USB Interface: USB Type-C
- Battery Operating Time: Approx. 6 Hours
- LED Flashlight
- Durability: IP54, 2m Drop Protection
- Weight: Approx. 380g
- Handheld



Excl VAT
R20 504.00

LC06 HANDHELD THERMAL MONOCULAR CAMERA

- High sensitivity thermal module with 160 x 120 resolution
- NETD < 35 mK • Pixel Interval: 17μm
- FOV: 24.7° x 18.7° • Detection Range: 219m
- Colour Palettes: Black Hot, White Hot, Red Hot, Fusion
- Leading thermal image processing technology: Adaptive AGC, DDE, 3D DNR
- 720 x 540 resolution 0.2-inch LCOS display
- Built-in rechargeable lithium battery
- Up to 10 hours continuous operation
- Wi-Fi hot spot
- USB Interface



Excl VAT
R9 152.00

LH19 HANDHELD THERMAL MONOCULAR CAMERA

- 384 x 288 resolution, 12 μm, high sensitivity detector
- Adaptive AGC, DDE, 3D DNR, NETD less than 35 mk
- 1280 x 960 resolution 0.4-inch LCOS display
- 19mm Lens • FOV: 13.8° x 10.4°
- Detection Range: 897m
- Pixel Interval: 12μ
- Built-in rechargeable lithium battery
- Up to 7.5 hours continuous running
- Wi-Fi hot spot
- Type-C Interface
- Palettes: Black Hot, White Hot, Red Hot, Fusion
- Frame Frequency: 50Hz
- USB Interface



Excl VAT
R19 895.00

FLIR CM174

- Thermal Image Resolution: 4800 pixels (60 x 80)
- Thermal Sensitivity: 150mK
- Field of View: 38.6° x 50.0°
- Colour Palettes: Iron, Rainbow, Grayscale
- Image Frame Rate: 9Hz
- Temperature Measurement: Centre Point of Thermal Image
- Temperature: -25°C ~ 150°C
- Temperature Distance to Spot Ratio: 30:1
- Spectral Response: 8 ~ 14μm
- Class 1 Laser
- Electrical Measurement:
- AC/DC Voltage: 1000V
- LoZ Mode AC/DC Voltage: 1000V
- AC/DC Current: 600A
- Inrush AC Current: 600A
- Frequency: 60kHz • Resistance: 6000Ω
- Continuity: 600Ω • Capacitance: 1000μF
- Diode



Excl VAT
R7 268.00

FLIR ONE IOS.

- Thermal Sensor: Pixel Size: 12μm, 8~14μm Spectral Range
- Thermal Resolution: 160 x 120
- HFOV/VFOV: 55°
- Fixed Focus
- Thermal Sensitivity: 150mK
- Emissivity settings: Matte, Semi-Matte, Semi-Glossy, Glossy, Reflected background temperature is 22°C
- Shutter: Manual / Automatic • Capture Modes: Video, Photo, Time Lapse
- Palettes: White Hot, Hottest, Coldest, Iron, Rainbow, Contrast, Ercic, Lava and Wheel
- Visual Resolution: 1440 x 1080
- Frame Rate: 8.7Hz
- Scene Dynamic Range: -20°C ~ 400°C



Excl VAT
R7784.00

FLIR VP52

- Voltage Range: 90 ~ 1000V
- Frequency Range: 45 ~ 65Hz
- Built-in Flashlight
- Vibrating Indication
- On/Off Switch
- High/Low Sensitivity Mode
- Red LED Alarms



Excl VAT
R340.00

a member of the **Hudaco** group